



Conductive Conductivity Measuring Cells



measuring
•
monitoring
•
analysing

ACS-Z
COMPACT-LINE



- Conductive measuring system (two-electrode system)
- Measuring range:
 - 0.05 ... 10 $\mu\text{S}/\text{cm}$ (K = 0.01 1/cm)
 - 1 ... 1000 $\mu\text{S}/\text{cm}$ (K = 0.1 1/cm)
 - 10 $\mu\text{S}/\text{cm}$... 15 mS/cm (K = 1.0 1/cm)
- Body material PVDF
- G $\frac{3}{4}$ A BSP thread
- Rated pressure to 16 bar
- Thermostability up to 135 °C
- Electrode material stainless steel 1.4571 (at K = 1.0 1/cm graphite)
- Integrated temperature sensor Pt 100



KOBOLD companies worldwide:

ARGENTINA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLUMBIA, CZECHIA, DOMINICAN REPUBLIC, EGYPT, FRANCE, GERMANY, GREAT BRITAIN, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, ROMANIA, SINGAPORE, SOUTH KOREA, SPAIN, SWITZERLAND, TAIWAN, THAILAND, TUNISIA, USA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
Head Office:
+49(0)6192 299-0
+49(0)6192 23398
info.de@kobold.com
www.kobold.com

Description

The conductivity measuring cells are used with transducer model ACM-Z. The cells comprise a screw-in body made of plastic (PVDF) and electrodes embedded in this body. A temperature sensor Pt100 for temperature detection and compensation is also integrated. The electrodes are manufactured from Stainless Steel or special graphite and are delivered with different cell constants and thus various measuring ranges. The electrical connection of the cells is carried out with plug connections.

Typical Applications

K = 0.01 / K = 0.1


Pure and ultra-pure water, pharmaceutical industry, chemical industry, foodstuff technology, chip manufacture, ion exchanger plants and reverse osmosis plants.

K = 1.0

- media separation
- drinking water purification
- wastewater checks/treatment

Dimensions


Cell constant
K = 0.01; K = 0.1 1/cm



Technical Details

- Measuring ranges:
- 1: 0.05... 10 μ S/cm (K = 0.01 1/cm)
 - 2: 1... 1000 μ S/cm (K = 0.1 1/cm)
 - 3: 10 μ S/cm... 15 mS/cm (K = 1.0 1/cm)
- Measuring surfaces:
- stainless steel 1.4571 for measuring ranges 1 and 2
 - spezial graphite for measuring range 3
- Body material: PVDF (Polyvinylidenfluoride)
- Thermostability: 135 °C (at 1 bar)
- Rated pressure: 16 bar (at 25 °C)
- Linear dependence of pressure and temperature*
- Screw-in thread: G 3/4 A
- Temperature sensor: Pt 100 integrated
- Thermostability of cable ACK-Z: -5... +80 °C

Cell constant
K = 1.0 1/cm



Order Details Measuring Cell (Example: ACS-Z 1 T 1 G)

Model	Measuring range	Temperature sensor	Electrical connection	Process connection
ACS-Z	1 = Measuring range 1: 0.05... 10 μ S/cm (K = 0.01 1/cm) 2 = Measuring range 2: 1... 1000 μ S/cm (K = 0.1 1/cm) 3 = Measuring range 3: 10 μ S/cm... 15 mS/cm (K = 1.0 1/cm)	T = with Pt 100	1 = 1 plug and socket connection	G = thread G 3/4 A

Order Details Cable

Model	Length
ACK-Z	05 = 5 m 10 = 10 m 15 = 15 m 20 = 20 m 25 = 25 m