



Vibrating Level Switches for Bulk Goods



measuring
•
monitoring
•
analysing

NVI



- Pressure: max: max. 25 bar
- Temperature: max. 160°C
- Connection: 1½ G or NPT
- Material: stainless steel
- Easy to install
- Suited for universal use
- For density > 0,05 kg/dm³
- Self-cleaning



KOBOLD companies worldwide:

ARGENTINA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLUMBIA, CZECHIA, DOMINICAN REPUBLIC, EGYPT, FRANCE, GERMANY, GREAT BRITAIN, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, ROMANIA, SINGAPORE, SOUTH KOREA, SPAIN, SWITZERLAND, TAIWAN, THAILAND, TUNISIA, USA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
Head Office:
+49(0)6192 299-0
+49(0)6192 23398
info.de@kobold.com
www.kobold.com

Description

The KOBOLD NVI level switch is a mechanical system that is made to resonate by an electronic switching operation. When the probe is covered by a medium, the vibrations are damped. This change in the resonance frequency is converted to a switching signal by electronic means.

Applications

The combined vibrating switch can be used in powdery media and granular materials. The medium to be measured should have a density of at least 0.05 kg/dm³. The single rod design prevents deposit formation. The rod is self-cleaning, as the vibrations shake off the medium.

The combined vibrating switch is in successful service in the following applications:

- Plastics industry: powders and granular material
- Chemical industry: powders, pellets and crystals
- Foodstuffs: grain, maize, flour, animal feed
- Paper making: cellulose, wood chips
- Recycling: plastic granules, paper shavings
- Power stations: flue dust, lime, coal
- Stones and earth: coal, stone powder
- Building and construction industry: cement, sand, lime


Selection criteria

The system is set at the factory for a medium density of 0.3 kg/dm³. When the medium has a low density, the sensitivity can be set to this density with a DIP switch. The level switch is inserted in the medium to be monitored for this purpose.

Technical Details

Probe length:	207 mm extended version on request
Process connection:	G 1½ or 1½ NPT
Housing material:	Aluminum, powder coated
Material for wetted parts:	1.4571 (AISI316Ti)
Sensor surface:	bright
Medium temperature:	-30°C... +110°C standard -30°C... +160°C high temperature
Ambient temperature:	-40°C... +60°C
Maximum pressure:	25 bar
Minimum density of medium:	0.05 kg/dm ³
Max. grain size:	10 mm
Max. load:	Force: 500 N Torque: 100 Nm
Response time:	< 1.8 s or 5 ±1.5 s with covered electrode < 2 s or 5 ±1.5 s with non covered electrode
Output:	changeover contact 250 V _{AC} /8A
Power supply:	20...255 V _{AC/DC} ; ≤ 2.5 VA/2 W
Electrical connection:	M20 x1,5
Protection:	IP 67
Weight:	1.9 kg

Dimensions



Order Details (Example: NVI-1 305 R)

Model	Version	Power supply	Connection
NVI-	1 = standard 2 = high temperature	305 = 20...255 V _{AC/DC}	R = G 1½ N = 1½ NPT