



## Immersion and Insertion Resistance Thermometers with Connecting Lead



measuring  
•  
monitoring  
•  
analysing



- Measuring ranges: -20 ... +350 °C
- Bulbs made of stainless steel 1.4571
- Pt 100 sensor category B (category A optional)
- Connection: cable
- Steam proof version (for sterilization processes)

T2



KOBOLD companies worldwide:

ARGENTINA, AUSTRIA, BELGIUM, CANADA, CHILE, CHINA, COLOMBIA, CZECHIA, FRANCE, GERMANY, GREAT BRITAIN, INDIA, IRAN, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, SINGAPORE, SLOVAKIA, SPAIN, SWITZERLAND, THAILAND, USA, VENEZUELA, VIETNAM

KOBOLD Messring GmbH  
Nordring 22-24  
D-65719 Hofheim/Ts.  
☎ +49(0)6192 299-0  
Fax +49(0)6192 23398  
E-Mail: info.de@kobold.com  
Internet: www.kobold.com

**Model:**  
TWE-6..7..8

**Description**


The immersion and insertion resistance thermometers comprise a rugged sensor made of stainless steel. Depending on the version, the connecting leads are suitable for dry or moist rooms. The junction between connecting lead and protective tube is strain relieved. Pt100 temperature sensors according to IEC 751, category B are used as standard. Other categories or versions are also available with Pt 500 and Pt 1000. These sensors are available as single or double resistance thermometers.

The immersion and insertion resistance thermometers are available in two-, three- or four-wire circuitry.

**Applications**

Immersion and insertion resistance thermometers are particularly suited for measuring temperature in liquid and gaseous media. Areas of application are to be found in heating installation, furnace and apparatus construction, machine construction and building installations as well as in industry in general.

**Immersion/insertion resistance thermometer**  
angular sensor




Bulb made of stainless steel 1.4571, Ø 6 mm Connecting lead: stainless steel braided 0.22 mm <sup>2</sup> Standard cable length: 2500 mm, others upon request Temperature range: -20 ... +350 °C				
Model number	Immersion length	Sensor type/category	Wiring	Connection cable
TWE-664 060.. TWE-664 xx0..	60 mm other length	..1.. = 1 x Pt100, category B ..2.. = 2 x Pt100, category B	..2..=2-wire ..3..=3-wire ..4..=4-wire*	..E = braided st. steel cable (standard 2.5 m)

Please specify special lengths for bulb and/or cable in writing

\*with 1 x Pt 100 only


**Immersion/insertion resistance thermometer**  
steam proof version



Bulb made of stainless steel 1.4571, Ø 6 mm Connecting lead: PTFE insulated, 0.22 mm <sup>2</sup> Standard cable length: 2500 mm, others upon request Temperature range: -20 ... +150 °C				
Model number	Immersion length	Sensor type/category	Wiring	Connection cable
TWE-764 100.. TWE-764 xx0..	100 mm other length	..1.. = 1 x Pt100, category B ..2.. = 2 x Pt100, category B	..2..=2-wire ..3..=3-wire	..P = PTFE insulated cable (standard 2.5 m)

Please specify special lengths for bulb and/or cable in writing

**Immersion/insertion resistance thermometer**  
straight version



Bulb made of stainless steel 1.4571, Ø 6 mm Connecting lead: PTFE insulated, 0.22 mm <sup>2</sup> , with bend protection or PVC-insulated, 0.22 mm <sup>2</sup> without bend protection · Standard cable length: 2500 mm, others upon request Temperature range: PTFE cable: -20 ... +260 °C; PVC cable: -20 ... +70 °C				
Model number	Immersion length	Sensor type/category	Wiring	Connection cable
TWE-864 050.. TWE-864 100.. TWE-864 200.. TWE-864 xx0..	50 mm, 100 mm, 200 mm, other length	..1.. = 1 x Pt100, category B ..2.. = 2 x Pt100 category B	..2..=2-wire ..3..=3-wire ..4..=4-wire*	..P = PTFE insulated cable (standard 2.5 m) ..C = PVC insulated cable (standard 2.5 m)

Please specify special lengths for bulb and/or cable in writing

\*with 1 x Pt 100 only

T2