



- Especially suited for multiphase media
- Mechanical density measuring and monitoring of liquids in pipes
- No bypass required
- Robust design
- Clear 90°-scale
- Transmitter optional with HART® or PROFIBUS-PA



KOBOLD companies worldwide:

ALGERIA, ARGENTINA, AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLOMBIA, CZECHIA, DOMINICAN REPUBLIC, EGYPT, FRANCE, GERMANY, GREAT BRITAIN, INDIA, INDONESIA, IRAN, ITALY, MALAYSIA, MEXICO, MOROCCO, NETHERLANDS, PERU, PHILIPPINES, POLAND, ROMANIA, SINGAPORE, SLOVAKIA, SPAIN, SWITZERLAND, THAILAND, TUNISIA, USA, VENEZUELA, VIETNAM

KOBOLD Messring GmbH  
 Nordring 22-24  
 D-65719 Hofheim/Ts.  
 ☎ +49 (0) 61 92 299-0  
 Fax +49 (0) 61 92 233 98  
 E-Mail: info.de@kobold.com  
 Internet: www.kobold.com

**Model:**  
 DWF



**Description**

The displacer rod, which is attached to a measuring spring by a chain, immerses into the liquid and is subject to a buoyant force proportional to the mass of the displaced liquid.

Every change in the weight of the rod corresponds to a change in the length of the spring and is therefore a measure of the liquid level. The longitudinal expansion of the spring, i.e. the travel of the rod, will be transmitted from the measuring space to the indicator unit by means of a magnetic coupling. The basic version of the indicator unit consists of a scale with a pointer for displaying the liquid level. As an option, the indicator unit may be equipped with electrical transmitters for remote display or with limit switches.

If the device cannot be installed from above, because, for example, a stirrer is mounted in the container, a special displacement vessel is available for lateral installation.

Since the buoyancy of the displacer rod depends on the density (g/L or kg/m<sup>3</sup>) of the measured medium, it must have been designed for the specific liquid to be measured.

**Application examples**

- Density metering, -monitoring, and control of liquid media in pipes.
- The meter's design as a pure mechanical device is excellent for processes under difficult and rough operating conditions.
- The device is available with additional electrical equipment for process monitoring and control.
- A large spectrum of wetted materials
- Magneto-resistive signal transmission
- High-temperature application (option)
- High-pressure application (option)
- Excellent heat tracing technology (option)

**Technical Data**

Density range:	700 g/L – 1900 g/L
Measuring span:	50 g/L – 600 g/L
Materials sensor:	Stainless steel, Hastelloy other materials on request
Materials display:	Aluminum (stove-enameled), Stainless steel (option)
Process connection:	DN 25 ASME 1" (TSK1) DN 50 ASME 2" (TSK 2, 3) flange acc. EN 1092, ASME B16.5, DIN2512, special connections on request
Nominal pressure:	PN 16, ASME CI150 (standard) higher pressure rates up to 400 bar optional
Process temperature:	-20 °C... +150 °C
Ambient temperature:	-20 °C... +80 °C -20 °C... +65 °C (with switch) -40 °C... +70 °C (Transmitter)
Ingress protection	
Sensor:	IP 65/67 (EN60529)
Transmitter:	IP 20 (EN60529)

**Flow range**

Model	Flow range*
1	2500 L/h
2	5000 L/h
3	10000 L/h

*Reference condition: according to IEC 770:  
Water at 20 °C*

Outputs: inductive switch  
 inductive switch (safety design)  
 microswitch  
 others on request

Transmitter: ES with HART®-protocol  
 ES with HART®-protocol and  
 2 NAMUR-switches  
 ES with HART®-protocol and  
 1 NAMUR-switch /  
 1 pulse output  
 ES with Profibus-PA

Power supply: 14 - 30 V<sub>DC</sub>

Output: passive, galvanically isolated

Currency: 4-20 mA

Binary 1 and 2: U<sub>i</sub>=30 V, I<sub>i</sub>=20mA, P<sub>i</sub>=100 mW

**Accuracy**

Span	Accuracy
50 g/L	± 1,25 g/L
100 g/L	± 2,00 g/L
200 g/L	± 3,00 g/L
300 g/L	± 4,50 g/L
600 g/L	± 6,00 g/L

± 0,2% with transmitter (ES)

**Certification**

Explosion protection: BVS 03 ATEX HIB 112  
 (Sensor)

Explosion protection: DMT 00 ATEX E 075  
 (Transmitter)

Type of protection: II 2G EEx ia IIC T6



